

Coaxial Cable Connector 24_BNT-50-3-1/103_N

Description

Straight bulkhead cable feed through

Interface standards
SUHNER-BNT



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 3 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0234 kg

Environmental Data

Operating temperature -50 °C to 125 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00048069
Catalogue drawing DCA-00009150
Assembly instruction DOC-0000179264
Mounting hole DOU-00008751

Ordering Information

Single package 24_BNT-50-3-1/103_NE

Additional Information

Suitable cables G_03332

Remarks

Triaxial Connector