
# **Data Sheet**

# Coaxial PCB Connector 82\_MCX-S75-0-2/111\_N

# Description

Straight PCB jack

Interface Standards IEC 60169-36\_CECC 22220



# **Technical Data**

Electrical Data	
Impedance	75 Ω
Interface frequency max.	6 GHz
Mechanical Data	
Board mounting type	edge mount
Weight	0.0009 kg
Environmental Data	
Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

## **Related Documents**

Outline drawing Catalogue drawing

DOU-00013375 DCA-00013377

# Ordering Information

Single package Bulk 100 pcs package 82\_MCX-S75-0-2/111\_NE 82\_MCX-S75-0-2/111\_NH

## Remarks

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

